

# JET-shear High Shear In-tank Mixer

Efficiently and consistently emulsify, dissolve and disperse ingredients within your process. The JET-shearhas impellers at the top and bottom of the work head that draws in material while centrifugal force moves the media out creating a mechanical shear. Reduce processing time, increase quality and consistency of the blend, and increase throughput with the JET-shear.

Ampco's in-tank mixers are used to hydrate, homogenize, disperse and emulsify products covering a wide range of applications in food, personal care, chemical, and pharmaceutical industries. The multiple interchangeable stainless steel work heads are designed for 3A and CIP. The JET-shearcan be used in open and closed tanks, drums or tote processing up to 5000 gallons / 22730 liters.

JS125

JS150

JS200

JS300

## **JET-SHEAR FEATURES**

- Emulsion to less than 10 microns
- Max volumes up to 5000 gallons
- · 316 stainless steel shaft
- 304 stainless steel bearing frame
- Multiple 316 stainless work head styles available
- Work heads can be interchanged
- Designed to 3A standards
- CIP-able
- Multiple mounting configurations
- Multiple shaft lengths
- Custom options available

## **PRODUCT SPECIFICATIONS**

Standard Bearing Frame Sizes	Max Shaft Length	Standard Shaft Diameter	Workhead Diameter
JS125	48″	1.25″	2.5″-4.0″
J\$150	60″	1.50″	3.5″-4.0″
JS200	84″	2.00″	3.5"-4.5"
JS225	84″	2.25″	4.5″-6.0″
12300	96″	3.00″	5.0"-8.0"
JS400	96″	4.00″	6.0"-10.0"

\* Custom options are available; contact Ampco Pumps for additional information



### **MOUNTING OPTIONS**

In-tank mixing applications demand a variety of mounting design options. No matter the size of your tank, drive type or unique processing application, we have custom stands and tank mounting options to offer maximum flexibility.



### **WORK HEAD OPTIONS**

Selecting the correct work head or work head combinations to fit your process is key. We have engineered a wide variety of interchangeable work heads and work head combinations to offer maximum flexibility and efficiency for:

- Mixing
- Dispersing
- Hydration

- De-agglomeration
- Particle Size Reduction
- Emulsification



Ampco Pumps Company 2045 W. Mill Road Glendale, WI 53209 Phone: 800.737.8671 www.ampcopumps.com Gewerbepark West II 7 76863 Herxheim Germany Phone: +49 7276 5058515 info@ampcopumps.de

Ampco Pumps GmbH